



304 Smokey Lane North Little Rock, Arkansas 72117 Phone: (501) 945-0354 FAX: (501) 945-0370
www.StreetandPerformanceElectronics.com

Helix Power Tower PLUS **Installation Instructions**

(1989-1994 Mitsubishi Eclipse 1.8L 4G37
1995-1998 Eagle Talon 2.0L Non-Turbo "Y" Part #93001)

Important! Read all instructions before you begin installation.

1. Unclamp and remove air inlet from throttle body.
2. Unbolt throttle cable bracket from intake manifold.
3. Remove four bolts that secure throttle body to intake manifold.
4. Install new gasket, Helix Power Tower PLUS (engraved side towards throttle body), another gasket and throttle body onto intake manifold. Use the two longest original bolts in the short side of throttle body and use the supplied longer bolts in the long side of throttle body. Torque to 15 ft/lb.
5. Install throttle cable extender bracket onto intake manifold. Use supplied longer bolts to secure assembly to mounting bracket. Torque to 12 ft/lb. Install air inlet assembly on the throttle body. Tighten clamp to throttle body.



Parts List

- 1 Helix Power Tower PLUS
- 2 Gaskets
- 2 8mmx90mm bolts
- 2 8mm flat washers
- 2 6mmx35mm bolts
- 2 6mm washers
- 1 Throttle cable extender